proxSafe® maxx

We Manage Your Keys

proxSafe is the first choice wherever keys or assets have to be managed automatically.

With proxSafe systems your keys are safely stored and will only be issued to authorized persons. Users and keyTags are identified contactlessly and therefore quickly and reliably. All transactions are recorded automatically.

proxSafe maxx – Space Saving and Elegant

proxSafe maxx is a key management system that combines the advantages of a superior electronic system with an architecturally designed appearance. The smart design allows application in all situations where the visual appearance counts as well as reliable technology.

Thanks to the automatic roller shutter this cabinet needs very little space for operation. The cabinet opens for authorized transactions and closes automatically.

Modular System

A proxSafe maxx cabinet manages up to 32 keys. Several cabinets can be combined to form a large complete system. Together with the proxSafe Terminal and the proxSafe Commander software this is an easy-to-install key management system which can be adapted to changing requirements at any time.

Reliable Technology

The generous resident memory of the user terminal allows operation even if the network fails and a back-up battery bridges in case of power failures. An emergency key is provided in order to allow manual access to the cabinets and keyTags by management if necessary.

100% Maintenance Free

The keyTags and slots are designed for rugged operation. There are no electrical contacts on the keyTags.
Dirt, corrosion or wear by daily operation are impossible. The proxSafe keyTags and corresponding slots require no maintenance.

Technical Data

Dimensions (mm):	513 x 600 x 187 (20.2 x 23.6 x 7.4 inches)
Housing Material:	sheet steel, powder-coated ASA, PC
Weight:	approx. 17 kg (37.5 lbs)
Operating Temperature:	-5…50 °C (23...122 °F) non-condensing; for indoor use
Closing Force of Roller Shutter:	max. 30 N
Voltage Supply:	13.8 V/DC (one proxSafe power supply unit for 2 cabinets)
Current Consumption:	max. 3.0 A
Back-up Battery:	2300 mAh (operating time min. 4 hours; up to 24 hours when in power save mode)

The RFID Company

deister electronic

For more information contact a proxSafe Business Partner or visit **www.proxSafe-usa.com** Technical data subject to change without notice at any time. The product conforms to CE-regulations. All rights reserved. © Copyright 2007 by deister electronic.

ps_maxx_info_en rev by MM.odt
V12/11/08 CL/IO/BF