

proxSafe® pillar S

We Manage your Assets

proxSafe is the first choice wherever keys or assets have to be managed automatically.

With proxSafe systems your keys are safely stored and will only be issued to authorized persons. Users and keyTags are identified contactlessly and therefore quickly and reliably. All transactions are recorded automatically.

Locker System proxSafe pillar

proxSafe pillar is a safekeeping system for automatic issue and return of valuables, documents and key rings. Every column consists of a number of automatic lockers plus a service locker for installation and emergency release.

Modular System Design

pillar S systems are composed of one terminal pillar and up to seven locker pillars. Many combinations are possible in order to accommodate user needs initially, and as they may change over time.

Intelligent locker design

Size and arrangement of the lockers is optimized for daily use. The design is smart and elegant, so the system can be installed in an architectural environment.

Easy-to-use

proxSafe pillar is operated with a proxSafe Terminal. After a user has been identified and has selected a locker, the corresponding locker will be unlocked. This is indicated by an LED. Also upon return of the contents the locker is marked with an LED in order to guide the user to the right position.

Content Monitoring

proxSafe pillar is equipped with automatic content monitoring. There is a proxCylinder in every locker which identifies the contents certainly and reliably.

Fail-safe Opening

The drawers of the proxSafe pillar system are not fully released after only electronic command but will require the authorized user to touch the door. Thus unintended opening of the drawers can be avoided.

The proxSafe pillar S is the secure, reliable, easy to use, and safest solution for safekeeping and asset management.



**proxSafe pillar S11JT and 7 x S14J
(locker installation with 109 lockers and a proxSafe Terminal)**

Technical Data

Outer dimensions per column (inches):

H 75.6 x B 9.8 x D 11.8

Material:

sheet steel St. 12.03,
RAL 9005/9006

Inner dimensions:

(height x width x depth in in)

locker pillar S 14J

12 lockers 3.7 x 6.5 x 11.6
2 lockers 5.6 x 6.5 x 11.6

terminal pillar S 11JT

9 lockers 3.7 x 6.5 x 11.6
2 lockers 5.6 x 6.5 x 11.6
prepared for installation
of a proxSafe Terminal

locker pillar S 12P

12 lockers 4.7 x 6.5 x 11.6

terminal pillar S 10PT

10 lockers 4.7 x 6.5 x 11.6
prepared for installation
of a proxSafe Terminal

Voltage supply:

90-250 V/DC

Current consumption:

2300 mAh (with back-up battery)